

**PVC Pipe cement** 

## Version number: GHS 2.0 (2021-10-25)

Replaces version: GHS 1 (2020-11-11)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier	
	Trade name	PVC Pipe cement
	SDS-Ref	061356
1.2	Relevant identified uses of the substance or mixture and uses advised against	
	Relevant identified uses	Adhesive
1.3	Details of the supplier of the safety data sheet	Steinbach International GmbH L. Steinbach Platz 1 4311 Schwertberg Austria Telephone: +43 7262 61431 1000 e-Mail: info@steinbach-group.com e-Mail (competent person): sdb@steinbach-group.com

#### **Emergency telephone number** 1.4

Country	Name	Postal code/city	Telephone	Opening hours
Austria	Vergiftungsinformationszentrale	1090 Wien	+43 1 406 4343 (24h)	
United King- dom	National Poisons Information Service		111 (24h)	

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.6	flammable liquid	2	Flam. Liq. 2	H225
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic ef- fects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word Danger
- Pictograms

GHS02, GHS07



Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

### Version number: GHS 2.0 (2021-10-25)

- Precautionary stateme	ents				
P101	If medical advice is needed, h	ave product container or label at hand.			
P102	Keep out of reach of children.				
P210	Keep away from heat, hot sur	faces, sparks, open flames and other ignition sources. No smoking.			
P271 Use only outdoors or in a well-ventilated area.					
P403+P235	Store in a well-ventilated place. Keep cool.				
P501	Dispose of contents/container	r to hazardous or special waste collection point.			
- Supplemental hazard	information				
EUH066 Repeated exposure may cause skin dryness or cracking.					
- Hazardous ingredient	s for labelling	Ethyl acetate; Butanone; Methyl acetate; Acetone			

# 2.3 Other hazards

Of no significance

# **SECTION 3: Composition/information on ingredients**

# 3.1 Substances

Not relevant (mixture).

# 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Classification acc. to GHS	Pictograms	Wt%
Ethyl acetate	CAS No 141-78-6	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336		25 - < 50
	EC No 205-500-4			
	Index No 607-022-00-5			
	REACH Reg. No 01-2119475103-46-xxxx			
Butanone	CAS No 78-93-3	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336		10 - < 25
	EC No 201-159-0	,		
	Index No 606-002-00-3			
	REACH Reg. No 01-2119457290-43-xxxx			
Methyl acetate	CAS No 79-20-9	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336		10 - < 25
	EC No 201-185-2			
	Index No 607-021-00-X			
	REACH Reg. No 01-2119459211-47-xxxx			



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC Pipe cement**

## Version number: GHS 2.0 (2021-10-25)

## Replaces version: GHS 1 (2020-11-11)

Name of substance	Identifier	Classification acc. to GHS	Pictograms	Wt%
Acetone	CAS No 67-64-1 EC No 200-662-2 Index No 606-001-00-8 REACH Reg. No 01-2119471330-49-xxxx	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336		10 - < 25

For full text of abbreviations: see SECTION 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

## General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Take off immediately all contaminated clothing. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

## Following inhalation

Mouth to mouth resuscitation should be avoided. Use alternative methods, preferably with oxygen or compressed air driven apparatus. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In all cases of doubt, or when symptoms persist, seek medical advice.

### Following ingestion

Rinse mouth with water (only if the person is conscious). Let be drunken in little sips: 0, 1-0, 2l Water. Do NOT induce vomiting.

# 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

# 4.3 Indication of any immediate medical attention and special treatment needed

None.

# **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

# 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

## Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

Version number: GHS 2.0 (2021-10-25)

# 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

# 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

# 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

## Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use only in well-ventilated areas. Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

# 7.2 Conditions for safe storage, including any incompatibilities

## Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

### Version number: GHS 2.0 (2021-10-25)

## - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

### Control of effects

- Protect against external exposure, such as

High temperatures, Frost, UV-radiation/sunlight

## - Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

### Packaging compatibilities

Professional use: Only packagings which are approved (e.g. acc. to ADR) may be used. Consumer use (private households): Keep only in original container.

### Conditions of storage

Keep container tightly closed in a cool place. Protect from sunlight. Keep away from children.

# 7.3 Specific end use(s)

There is no additional information.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Coun try	Name of agent	CAS No	lden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m <sup>3</sup> ]	Nota- tion	Source
EU	ethyl acetate	141-78- 6	IOELV	200	734	400	1,468				2017 / 164/ EU
EU	acetone	67-64-1	IOELV	500	1,210						2000 /39/ EC
EU	ethyl methyl ketone	78-93-3	IOELV	200	600	300	900				2000 /39/ EC
GB	ethyl acetate	141-78- 6	WEL	200	734	400	1,468				EH40 / 2005
GB	acetone	67-64-1	WEL	500	1,210	1,500	3,620				EH40 / 2005
GB	butan-2-one (methyl ethyl ketone)	78-93-3	WEL	200	600	300	899				EH40 / 2005
GB	methyl acetate	79-20-9	WEL	200	616	250	770				EH40 / 2003

Notation

Ceiling-C STEL ceiling value is a limit value above which exposure should not occur

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

Version number: GHS 2.0 (2021-10-25)

Replaces version: GHS 1 (2020-11-11)

Biological	limit valu	es							
Country	Nam	e of agent		Parameter	Notation	Identifier	Value	Source	
GB	but	an-2-one	eth	yl methyl ketone	•	BMGV 7	Ό μmol/l	EH40/200	
Relevant D	NELs of	components	of the mix	ture					
Name of su	bstance	CAS No	End- point	Threshold level	Protection goal, route of exposure	Used in	E	kposure time	
Ethyl ace	etate	141-78-6	DNEL	367 mg/m <sup>3</sup>	human, inhalatory	consumer (prive households)	ate chr	onic - systemic effects	
Ethyl ace	etate	141-78-6	DNEL	734 mg/m <sup>3</sup>	human, inhalatory	consumer (prive households)	ate acu	te - systemic ef fects	
Ethyl ace	etate	141-78-6	DNEL	367 mg/m <sup>3</sup>	human, inhalatory	consumer (prive households)	ate chr	onic - local ef- fects	
Ethyl ace	etate	141-78-6	DNEL	734 mg/m <sup>3</sup>	human, inhalatory	consumer (prive households)	ate acu	te - local effect	
Ethyl ace	etate	141-78-6	DNEL	37 mg/kg bw/day	human, dermal	consumer (prive households)	ate chr	onic - systemic effects	
Ethyl ace	etate	141-78-6	DNEL	4.5 mg/kg bw/day	human, oral	consumer (prive households)	ate chr	onic - systemic effects	
Butano	one	78-93-3	DNEL	106 mg/m <sup>3</sup>	human, inhalatory	consumer (prive households)	ate chr	chronic - systemic effects	
Butanc	one	78-93-3	DNEL	412 mg/kg bw/day	human, dermal	consumer (prive households)	ate chr	chronic - systemic effects	
Butanc	one	78-93-3	DNEL	31 mg/kg bw/day	human, oral	consumer (prive households)	ate chr	onic - systemic effects	
Methyl ac	cetate	79-20-9	DNEL	131 mg/m <sup>3</sup>	human, inhalatory	consumer (prive households)	ate chr	onic - systemic effects	
Methyl ac	cetate	79-20-9	DNEL	152 mg/m <sup>3</sup>	human, inhalatory	consumer (prive households)	ate chr	onic - local ef- fects	
Methyl ac	cetate	79-20-9	DNEL	44 mg/kg bw/day	human, dermal	consumer (prive households)	ate chr	onic - systemic effects	
Methyl ac	cetate	79-20-9	DNEL	44 mg/kg bw/day	human, oral	consumer (prive households)	ate chr	onic - systemic effects	
Aceto	ne	67-64-1	DNEL	200 mg/m <sup>3</sup>	human, inhalatory	consumer (prive households)		onic - systemic effects	
Aceto	ne	67-64-1	DNEL	62 mg/kg bw/day	human, dermal	consumer (prive households)		onic - systemic effects	
Acetor	ne	67-64-1	DNEL	62 mg/kg bw/day	human, oral	consumer (prive households)		onic - systemic effects	
Relevant P	NECs of	components	of the mix	ture					
Name of su	bstance	CAS No	End- point	Threshold level	Organism	Environment compartmen		kposure time	
Ethyl ace	etate	141-78-6	PNEC	0.24 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	shor	t-term (single ir stance)	
Ethyl ace	etate	141-78-6	PNEC	0.024 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	r shor	t-term (single ir stance)	
Ethyl ace	etate	141-78-6	PNEC	650 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatmo plant (STP)	ent shor	t-term (single ir stance)	
Ethyl acetate 141-78-6 PNEC 1.15		1.15 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sedin	nent shor	t-term (single ir stance)			



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

## Version number: GHS 2.0 (2021-10-25)

Г

Replaces version: GHS 1 (2020-11-11)

lame of substance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
Ethyl acetate	141-78-6	PNEC	0.115 <sup>mg</sup> /	aquatic organisms	marine sediment	short-term (single in stance)
Ethyl acetate	141-78-6	PNEC	0.148 <sup>mg</sup> /	terrestrial organ- isms	soil	short-term (single in stance)
Butanone	78-93-3	PNEC	55.8 <sup>mg</sup> /l	aquatic organisms	freshwater	short-term (single ir stance)
Butanone	78-93-3	PNEC	55.8 <sup>mg</sup> /I	aquatic organisms	marine water	short-term (single ir stance)
Butanone	78-93-3	PNEC	709 <sup>mg</sup> /l	aquatic organisms	sewage treatment plant (STP)	short-term (single in stance)
Butanone	78-93-3	PNEC	284.7 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single in stance)
Butanone	78-93-3	PNEC	284.7 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single in stance)
Butanone	78-93-3	PNEC	22.5 <sup>mg</sup> /kg	terrestrial organ- isms	soil	short-term (single in stance)
Methyl acetate	79-20-9	PNEC	0.12 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single i stance)
Methyl acetate	79-20-9	PNEC	0.012 <sup>mg</sup> /I	aquatic organisms	marine water	short-term (single in stance)
Methyl acetate	79-20-9	PNEC	600 <sup>mg</sup> /	aquatic organisms	sewage treatment plant (STP)	short-term (single in stance)
Methyl acetate	79-20-9	PNEC	0.128 <sup>mg</sup> / kg	aquatic organisms	freshwater sediment	short-term (single in stance)
Methyl acetate	79-20-9	PNEC	0.013 <sup>mg</sup> /	aquatic organisms	marine sediment	short-term (single in stance)
Methyl acetate	79-20-9	PNEC	0.042 <sup>mg</sup> /	terrestrial organ- isms	soil	short-term (single in stance)
Acetone	67-64-1	PNEC	10.6 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single in stance)
Acetone	67-64-1	PNEC	1.06 <sup>mg</sup> /I	aquatic organisms	marine water	short-term (single in stance)
Acetone	67-64-1	PNEC	100 <sup>mg</sup> /l	aquatic organisms	sewage treatment plant (STP)	short-term (single i stance)
Acetone	67-64-1	PNEC	30.4 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single in stance)
Acetone	67-64-1	PNEC	3.04 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single i stance)
Acetone	67-64-1	PNEC	29.5 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single i stance)

# 8.2 Exposure controls (professional use)

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

- Eye/face protection

Use safety goggle with side protection (EN 166).



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

### Version number: GHS 2.0 (2021-10-25)

## Skin protection

# - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

# Type of material

PVC: polyvinyl chloride, NR: natural rubber, latex

### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection: Full face mask (DIN EN 136).

## Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state	liquid				
Colour	transparent				
Odour	stinging				
Melting point/freezing point	<-50 °C				
Boiling point or initial boiling point and boiling range	>70 °C				
Flammability	not relevant (fluid)				
Lower and upper explosion limit	2.2 vol% - 11.5 vol%				
Flash point	-17 °C				
Auto-ignition temperature	800 °F (auto-ignition temperature (liquids and gases))				
pH (value)	6 - 9				
Kinematic viscosity	not determined				
Particle characteristics	no data available				
Oxidising properties	none				
Vapour pressure					
Vapour pressure	240 hPa at 20 °C				

## Density and/or relative density

Density	not determined				
Relative vapour density	<1 (air = 1)				
Other safety parameters					
Solubility(ies)	not determined				
Partition coefficient					
n-Octanol/water (log KOW)	this information is not available				



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

Version number: GHS 2.0 (2021-10-25)

# 9.2 Other information

Information with regard to physical hazard classes Other safety characteristics Temperature class (EU, acc. to ATEX) there is no additional information

T2 (maximum permissible surface temperature on the equipment: 300°C)

Replaces version: GHS 1 (2020-11-11)

# SECTION 10: Stability and reactivity

# 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

## If heated:

Risk of ignition

# 10.2 Chemical stability

See below "Conditions to avoid".

# 10.3 Possibility of hazardous reactions

No known hazardous reactions.

# 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

## 10.5 Incompatible materials

Oxidisers

# **10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

## Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

# Classification according to GHS (1272/2008/EC, CLP)

### Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Name of substance	CAS No	Exposure route	End- point	Value	Species
Ethyl acetate	141-78-6	dermal	LD50	>20,000 <sup>mg</sup> / <sub>kg</sub>	rabbit
Ethyl acetate	141-78-6	oral	LD50	5,620 <sup>mg</sup> / <sub>kg</sub>	rat
Ethyl acetate	141-78-6	oral	LD50	4,100 <sup>mg</sup> / <sub>kg</sub>	mouse
Butanone	78-93-3	oral	LD50	2,054 <sup>mg</sup> / <sub>kg</sub>	rat
Butanone	78-93-3	oral	LD50	3,000 <sup>mg</sup> / <sub>kg</sub>	mouse



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC Pipe cement**

#### Version number: GHS 2.0 (2021-10-25) Replaces version: GHS 1 (2020-11-11) CAS No Exposure End-Value Name of substance Species route point 79-20-9 Methyl acetate oral LD50 6,482 <sup>mg</sup>/<sub>ka</sub> rat Methyl acetate 79-20-9 dermal LD50 >2,000 <sup>mg</sup>/kg rat Acetone 67-64-1 oral LD50 5,800 <sup>mg</sup>/kg rat 67-64-1 3,000 mg/kgAcetone oral LD50 mouse

# Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

# Serious eye damage/eye irritation

Causes serious eye irritation.

# Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

## Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

# Carcinogenicity

Shall not be classified as carcinogenic.

## Reproductive toxicity

Shall not be classified as a reproductive toxicant.

## Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

# Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

# Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## Other information

Repeated exposure may cause skin dryness or cracking.

# 11.2 Information on other hazards

There is no additional information.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

# 12.2 Persistence and degradability

Data are not available.

# 12.3 Bioaccumulative potential

Data are not available.

# 12.4 Mobility in soil

Data are not available.

# 12.5 Results of PBT and vPvB assessment

Data are not available.



# **PVC** Pipe cement

### Version number: GHS 2.0 (2021-10-25)

## 12.6 Endocrine disrupting properties

None of the ingredients are listed.

## 12.7 Other adverse effects

Data are not available.

# **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

## Other disposal recommendations

Dispose of contents/container to hazardous or special waste collection point. Waste treatment of containers/packagings: Mixed municipal waste.

## Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SEC	TION 14: Transport information	
14.1	UN number or ID number	1133
	ADR/RID/ADN	UN 1133
	IMDG-Code	UN 1133
	ICAO-TI	UN 1133
14.2	UN proper shipping name	ADHESIVES
	ADR/RID/ADN	ADHESIVES
	IMDG-Code	ADHESIVES
	ICAO-TI	Adhesives
14.3	Transport hazard class(es)	
	ADR/RID/ADN	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	II (substance presenting medium danger)
	ADR/RID/ADN	II
	IMDG-Code	ll
	ICAO-TI	II
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations

# 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

# 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.



**PVC** Pipe cement

## Version number: GHS 2.0 (2021-10-25)

# Information for each of the UN Model Regulations

# Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

Particulars in the transport document	special provision 640C
Classification code	F1
Danger label(s)	3
Special provisions (SP)	640C
Excepted quantities (EQ)	E2
Limited quantities (LQ)	5 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33
Emergency Action Code	3YE
International Maritime Dangerous Goods Code	(IMDG) - Additional information
Marine pollutant	-
Danger label(s)	3
	•
Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	В
International Civil Aviation Organization (ICAO-	IATA/DGR) - Additional information
Danger label(s)	3
	<b>(</b>
Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# Relevant provisions of the European Union (EU) Restrictions according to REACH, Annex XVII

No	Name of substance	CAS No	Type of registration
3	PVC Pipe cement		1907/2006/EC annex XVII
40	Ethyl acetate		1907/2006/EC annex XVII
75	Ethyl acetate		2020/2081/EC annex XVII
40	Butanone		1907/2006/EC annex XVII
75	Butanone		2020/2081/EC annex XVII
40	Acetone		1907/2006/EC annex XVII
75	Acetone		2020/2081/EC annex XVII
40	Methyl acetate		1907/2006/EC annex XVII
75	Methyl acetate		2020/2081/EC annex XVII



# **PVC** Pipe cement

# List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

# None of the ingredients are listed.

# **Seveso Directive**

No	Dangerous s	substance/hazard categories	
P5c	flammable liquids (cat. 2, 3)		
Deco-Paint	Deco-Paint Directive		
VOC content 100 %			
Industrial Emissions Directive (IED)			

100 %

# VOC content

# Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

None of the ingredients are listed.

# Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed.

# Water Framework Directive (WFD)

None of the ingredients are listed.

# **Regulation on persistent organic pollutants (POP)**

None of the ingredients are listed.

# **National inventories**

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
Legend		

REACH Reg. REACH registered substances

# 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

# Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
1.3	Details of the supplier of the safety data sheet: Steinbach International GmbH L. Steinbach Platz 1 4311 Schwertberg Austria Telephone: +43 7262 61431 e-Mail: info@steinbach-group.com e-Mail (competent person): sdb@steinbach-group.com	Details of the supplier of the safety data sheet: Steinbach International GmbH L. Steinbach Platz 1 4311 Schwertberg Austria Telephone: +43 7262 61431 1000 e-Mail: info@steinbach-group.com e-Mail (competent person): sdb@steinbach-group.com	yes
2.3	Other hazards	Other hazards: Of no significance	yes
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		yes



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

## Version number: GHS 2.0 (2021-10-25)

## Replaces version: GHS 1 (2020-11-11)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevan
4.1	General notes: Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. In case of accident or if you feel unwell, seek medical advice immedi- ately (show the label where possible). Take off immediately all con- taminated clothing. In case of unconsciousness place person in the recovery position. Never give anything by mouth.	General notes: Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. In case of accident or if you feel unwell, seek medical advice immedi- ately (show the label where possible). Take off immediately all con- taminated clothing. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.	yes
4.1	Following skin contact: Wash with plenty of soap and water.		yes
6.3	Advice on how to clean up a spill: Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder	Advice on how to clean up a spill: Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Kieselgur (diatomite), Sand, Universal binder	yes
8.2	- Eye/face protection: Use safety goggle with side protection (EN 166).		yes
8.2		- Eye/face protection: Use safety goggle with side protection (EN 166).	yes
8.2	Hand protection: Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/im- permeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.		yes
8.2	Type of material: PVC: polyvinyl chloride, NR: natural rubber, latex		yes
8.2		- Hand protection: Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/im- permeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.	yes
8.2		Type of material: PVC: polyvinyl chloride, NR: natural rubber, latex	yes
8.2	- Other protection measures: Take recovery periods for skin regeneration. Preventive skin protec- tion (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.	- Other protection measures: Take recovery periods for skin regeneration. Preventive skin protec- tion (barrier creams/ointments) is recommended.	yes
8.2	Respiratory protection: In case of inadequate ventilation wear respiratory protection	Respiratory protection: In case of inadequate ventilation wear respiratory protection: Full face mask (DIN EN 136).	yes
9.1	Explosive limits	Lower and upper explosion limit: 2.2 vol% - 11.5 vol%	yes
9.1	Evaporation rate: not determined		yes
9.1	Lower explosion limit (LEL): 2.2 vol%		yes
9.1	Upper explosion limit (UEL): 11.5 vol%		yes
9.1		Kinematic viscosity: not determined	yes
9.1		Particle characteristics: no data available	yes
9.1		Oxidising properties: none	yes
9.1		Vapour pressure	yes
9.1		Density and/or relative density	yes



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

## Version number: GHS 2.0 (2021-10-25)

Replaces version: GHS 1 (2020-11-11)

Section	Former entry (text/value)	Actual entry (text/value)	Safety relevar
9.1	Vapour density: this information is not available		yes
9.1	Viscosity: not determined		yes
9.1	Explosive properties: none		yes
9.1	Oxidising properties: none		yes
9.2	Other information: There is no additional information.	Other information	yes
9.2		Information with regard to physical hazard classes: there is no additional information	yes
9.2		Other safety characteristics	yes
11.2		Information on other hazards: There is no additional information.	yes
12.7	Other adverse effects	Other adverse effects: Data are not available.	yes
14.1		ADR/RID/ADN: UN 1133	yes
14.1		IMDG-Code: UN 1133	yes
14.1		ICAO-TI: UN 1133	yes
14.2		ADR/RID/ADN: ADHESIVES	yes
14.2		IMDG-Code: ADHESIVES	yes
14.2		ICAO-TI: Adhesives	yes
14.3	Class: 3 (flammable liquids)		yes
14.3		ADR/RID/ADN: 3	yes
14.3		IMDG-Code: 3	yes
14.3		ICAO-TI: 3	yes
14.4		ADR/RID/ADN: II	yes
14.4		IMDG-Code: II	yes
14.4		ICAO-TI: II	yes
14.7	UN number: 1133		yes
14.7	Proper shipping name: ADHESIVES		yes
14.7	Class: 3		yes
14.7	Packing group: II		yes
14.7	UN number: 1133		yes



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

## Version number: GHS 2.0 (2021-10-25)

Replaces version: GHS 1 (2020-11-11)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relevant
14.7	Proper shipping name: ADHESIVES		yes
14.7	Class: 3		yes
14.7	Packing group: II		yes
14.7	UN number: 1133		yes
14.7	Proper shipping name: Adhesives		yes
14.7	Class: 3		yes
14.7	Packing group: II		yes
15.1		Restrictions according to REACH, Annex XVII: change in the listing (table)	yes
15.1		Regulation on persistent organic pollutants (POP): None of the ingredients are listed.	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16	Key literature references and sources for data: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU.Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	Key literature references and sources for data: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	yes

# Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
2017/164/EU	Commission Directive establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/ 322/EEC, 2000/39/EC and 2009/161/EU
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	indicative occupational exposure limit value
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic



according to Regulation (EC) No. 1907/2006 (REACH)

# **PVC** Pipe cement

## Version number: GHS 2.0 (2021-10-25)

Replaces version: GHS 1 (2020-11-11)

Abbr.	Descriptions of used abbreviations
PNEC	Predicted No-Effect Concentration
ppm	parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	short-term exposure limit
STOT SE	specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TWA	time-weighted average
VOC	Volatile Organic Compounds
vPvB	very Persistent and very Bioaccumulative
WEL	workplace exposure limit

# Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

# **Classification procedure**

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

# List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

# Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.